

# Bayoxide<sup>®</sup> Z active

## TECHNICAL DATA

### Zinc oxide

#### FEATURES

- Increases through drying for additives and topcoats
- Improves corrosion protection behavior and hardness
- Reduces yellowing of coatings
- Avoids “blooming” effect in wood coatings
- Can be used as a stabilizer in special adhesive for improved and longer storage

#### PHYSICAL CHARACTERISTICS

Appearance	Yellow powder
Density	5 g/cm <sup>3</sup> (20 °C)
Color	NA

#### APPLICATIONS

- Coatings
- Adhesives

#### DOSAGE

NA

#### STORAGE

Protect from the effects of weathering and store at temperatures between 5 and 30 °C in the original container. Once opened, containers should be resealed immediately after each removal of the product. Store indoors under normal dry conditions. Once opened, sacks should be resealed after use to prevent moisture absorption and contamination.

#### SAFETY

For further safety information please refer to our safety data sheet.

Contact us for more information

[www.borchers.com/contact](http://www.borchers.com/contact)

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.