

Borchi® Boost 510W

TECHNICAL DATA

Color booster developed to improve color acceptance for ready-made dispersions and tinting systems in water-based basecoat systems

FEATURES

- Improves color acceptance in medium to low polarity systems
- Strengthens tints with organic pigment dispersions and carbon blacks
- Reduces or eliminates color rubout
- 50% solid in water
- Can be incorporated as a post-add to the basecoat
- APEO- and VOC-free

PHYSICAL CHARACTERISTICS

Appearance	Liquid, yellow
Non-volatile content	50 %
pH	7 - 9.5
Density	1.09 g/cm ³ (20 °C)
Viscosity	Max. 1000 mPa.s
Solvent	Water

APPLICATIONS

- Water-based basecoats
- Organic pigment dispersions
- Carbon blacks

Contact us for more information

www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

DOSAGE

1 - 3% active on basecoat.

STORAGE

Protect from the effects of weathering and light. Store at temperatures between 5 and 30°C. Once opened, containers should be released immediately after each removal of the product.

SAFETY

Please refer to our safety data sheet for information relating to product safety.