

Borchi® Gol 3467

TECHNICAL DATA

Polyether modified polydimethylsiloxane, 100 % active, VOC-free

FEATURES

- Improved substrate wetting of water- and solvent-based systems
- Affinity to hydrophobic surfaces
- Reduces surface tension
- Improves wetting of difficult to wet and dirt contaminated substrates
- Prevents formation of defects from poor substrate wetting
- Suitable for clear and pigmented systems, as well as water- and solvent-based formulations

PHYSICAL CHARACTERISTICS

Appearance	Clear liquid
Non-volatile content	NA
pH	NA
Density	1.05 g/cm ³ (25 °C)
Viscosity	70 - 150 mPa.s ISO 3219 (A) (25 °C)
Color	Gardner: Max. 3 ISO 4630
Refractive Index	NA
Solvent(s)	NA

APPLICATIONS

- Coatings
 - Water-based
 - Solvent-based

Contact us for more information

www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

DOSAGE

Borchi® Gol 3467 used for substrate wetting should be added to the finished system. Recommended concentration is 0.05 to 1.50 wt. % on total formulation.

STORAGE

Protect from the effects of weathering and store at temperatures between 10 and 40 °C.

SAFETY

Please refer to our safety data sheet for information relating to product safety.