

Borchi® Gol 8701

TECHNICAL DATA

Silicone-free substrate wetting additive with good flow as well as excellent slip and over-coat ability

FEATURES

- Improves substrate wetting and flow
- Provides excellent slip without inter-coat adhesion interference
- Can be used in most solvent-based coating systems

PHYSICAL CHARACTERISTICS

Appearance	Clear liquid
Non-volatile content	48 - 52 % EN ISO 3251 (2h, 125 °C)
pH	NA
Density	0.98 g/cm ³ (20 °C)
Viscosity	20 - 40 mPa.s EN ISO 12058-1 (23 °C)
Color	(Hazen) Max. 40 ISO 2211
Refractive Index	NA
Solvent(s)	Methoxypropyl acetate

APPLICATIONS

- Coatings
 - Solvent-based

DOSAGE

The recommended dosage is 0.5 - 2.0 % of the total weight of the formulation depending upon the binder type. The exact dosage should be experimentally determined. Borchi® Gol 8701 is easy to use and can be added at any stage of the formulation; however, we recommend adding it near the end of the formula.

STORAGE

Protect from the effects of weathering and light. Store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product.

SAFETY

Please refer to our safety data sheet for information relating to product safety.

Contact us for more information
www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.