

Borchi® Burst DF 300

TECHNICAL DATA

Solvent- and silicone-free foam control agent for coatings

FEATURES

- Excellent defoamer
- Good compatibility
- Performs well over a wide range of pH values
- Successful at low concentrations
- Effective over a wide range of temperatures
- Helps with process productivity

PHYSICAL CHARACTERISTICS

Appearance	Pale yellow liquid
Chemical type	Alkoxane polymers
Water miscibility	Medium dispersibility
Fluidity	Viscosity not greater than 2000cPs @ 20° DIN 53019 100rpm
Cleanliness	No particles after screening through a 400µm aperture screen
Specific gravity @20 °C	0.98 - 1.02 g/ml
Active content	-99 %

**This information shows typical properties and does not constitute a specification.*

APPLICATIONS

- Gloss paints
- Wood coatings
- Pigment dispersions
- Matt and silk paints

Contact us for more information

www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

DOSAGE

Borchi® Burst DF 300 is usually added as received. The amount required depends of course on the particular application. A typical addition level would be between 0.05% and 0.5% in total, depending on the severity of the foam problem. The optimum quantity and points of addition are determined by laboratory trials.

STORAGE

Store in closed containers. Avoid extremes of temperature, keep between 5 °C and 30 °C. Avoid freezing and do not store in direct sunlight. Product has a shelf life of 12 months, however during this time period some phasing may occur. Remixing will ensure the product is suitable for use.

SAFETY

Please refer to our safety data sheet for information relating to product safety.