

Dispersant for Transparent Iron Oxide Pigments in Waterborne Coatings

Borchi® Gen 1750

- Ultimate transparency
- Low paste viscosity
- Shorter grind times compared to industry benchmarks

- High pigment loading
- Attains finer particle size faster
- Excellent storage stability

Ultimate Transparency

PY (2) 1K Acrylic Wood



PY (2) 2K Acrylic




Low Viscosity

35% Pigment Concentrate Resin-Free




Stable Viscosity Indicates a Quality Dispersion

Sicotrans Yellow L 1916



High Transparency

 ΔE^* Caused by Scattering





Dispersant for Transparent Iron Oxide Pigments in Waterborne Coatings

Borchi® Gen 1750

- Ultimate transparency
- Low paste viscosity
- Shorter grind times compared to industry benchmarks


- High pigment loading
- Attains finer particle size faster
- Excellent storage stability


Sicotrans Yellow L 1916

Pigment Concentrate Under Microscope




Smaller Particles Result in Better Transparency





Good Compatibility in Different Waterborne Coatings

with Cappoxyt Yellow 4212 & Cappoxyt Red 4437B





Enhances the Color of the Wood

Draw downs 200µm on Merbau Wood > 1 K Acrylate system / Cappoxyt Yellow L 4212





For more information, please reach us at borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processng, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing. Borchi is a dedemark of Borchers Americas

