

Zinc Nap-All[®] Lube Grade

TECHNICAL DATA

Rust inhibiting additive.

FEATURES

- Formulated specifically for the lubricant industry
- 10% Zinc Nap-All[®] Lube Grade has an oil carrier rather than the conventional solvent carrier usually contained in Zinc Naphthenate solutions
- Acts to inhibit the formation of sludge and reduces wear scar in petroleum lubricants for compressors and refrigerator systems

PHYSICAL CHARACTERISTICS

Appearance	Viscous brown liquid
Metal content	Zn: 9.80 - 10.20 %
Non-volatile content	76.0 - 96.0 %
Viscosity	300 - 500 mPa.s @ 210 °F, SUS
Color	<=18 Gardner GH
Flashpoint	>212 °F by Pensky- Martens Closed Cup

APPLICATIONS

- Lubricants
- Undercoating

DOSAGE

Please contact borchersinfo@milliken.com.

STORAGE

Protect from the effects of weathering and store at temperatures below 50 °C. Once opened, containers should be resealed immediately after each use.

SAFETY

Please refer to our safety data sheet for information relating to product safety.

Contact us for more information

www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.