

Borchi® Gol 5893

TECHNICAL DATA

Silicone-containing surface additive for solvent-free, solvent-based, and water-based systems

FEATURES

- Significantly decreases the surface tension of the system
- Improves the surface slip of the coating film
- Enhances flow and leveling and improves anti-blocking properties
- Good compatibility and low risk of cloudiness
- Improves substrate wetting and prevents cratering

PHYSICAL CHARACTERISTICS

Appearance	Clear-Light Cloudy Liquid
Active substance	100%
Viscosity	200-600 mPa·s (25°C)

APPLICATIONS

- Coatings
 - General Industrial
 - Wood
 - Automotive
 - Marine and Anti-Corrosive

DOSAGE

The recommended dosage is 0.05 to 0.3 % of the total weight of the formulation. The specific amount depends upon the binder type and which application is being used. The exact dosage should be experimentally determined. It can be added as supplied into the system or premixed. Dilution with a proper solvent before use can make it easier to dose.

STORAGE

Protect from the effects of weathering and light. Store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product.

SAFETY

Please refer to our safety data sheet for information relating to product safety.

Contact us for more information

www.borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.